(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 18 December 2003 (18.12.2003)

PCT

(10) International Publication Number WO 03/104711 A1

(51) International Patent Classification⁷: B30B 15/10 F16P 3/14,

(21) International Application Number: PCT/AU03/00707

(22) International Filing Date: 10 June 2003 (10.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

PS 2878 11 June 2002 (11.06.2002) AU 2002950078 10 July 2002 (10.07.2002) AU 2002951351 12 September 2002 (12.09.2002) AU

(71) Applicant and

(72) Inventor: DAVIES, Kevin, Stephen [AU/AU]; 11 Karo Place, Duncraig, Perth, Western Australia 6023 (AU).

(71) Applicant and

(74) Agent: HOLLIDAY, Neal, Joseph; Lord & Company, 4 Douro Place, West Perth, Perth, Western Australia 6005 (AU). (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A SAFETY SYSTEM



(57) Abstract: A safety system for use with a machine having a moving tool arranged to move through a known path of movement. The safety system is arranged to detect the presence of an obstruction in a region (20) around a portion of said path deemed to be hazardous. The safety system is characterised by comprising a light emitting means (16), a light receiving means (18) and a processing and control means. The light emitting means (16) is arranged to emit light generally parallel to the path of movement of the tool such that the region (20) is illuminated. The light receiving means (18) is arranged to receive light from the light emitting means (16) which has passed through the region (20). The processing and control means is arranged to receive information from the light receiving means (18) and determine whether an obstruction exists in the region (20) by the presence of one or more shadow regions cast on the light receiving means (18) by the obstruction and to control movement of the tool (12) dependent on the presence of obstructions in the region (12).



70 03/104711